

Strongboy

Specifications

The Strongboy offers a new dimension to the construction industry:

- **Simplistic & Robust**
- **Cost Effective**
- **Efficient**

The Strongboy is used as an adaption to an Adjustable Steel Prop to provide support to brickwork and other construction support structures.

Due to the Strongboy's robust dynamics, it can be fitted between courses on a double-skin, brick cavity wall from either side. Therefore providing a cost effective, efficient and safe construction component.

The Strongboy is zinc plated, this ensures a long life and low maintenance product.

All Strongboys are manufactured in accordance with ISO 9001:2000 quality system accreditation.

PRODUCT CODE	DESCRIPTION	WEIGHT (kgs)
SB6	Strongboy 6mm Lintel Support - with handle	5.8
SB6NH	Strongboy 6mm Lintel Support - without handle	5.8
SB8NH	Strongboy 8mm Lintel Support - without handle	5.8
SB8	Strongboy 8mm Lintel Support - with handle	5.8



Technical Information

- Max loading: 340kg.
- Max working height: 3m.
- Max spacing: 900mm.
- Patent registered.

The internet's No. 1 supply resource for BUILDERS, SCAFFOLDERS & HOMEOWNERS



Free delivery on all orders over £300 /



48hours delivery on items ordered before 12 pm