

Adjustable Steel Trench Struts

Specifications

- We offer an Adjustable Steel Trench Strut which features clawed end plates to support and grip the trench lining.
- All Adjustable Steel Trench Struts are thread rolled so there is no cutting away of material or loss of strength.
- Adjustable Steel Trench Struts are available in sizes No. 0 to No. 3.
- All Trench Struts are manufactured in accordance with our ISO 9001:2000 quality system accreditation.

PRODUCT CODE	DESCRIPTION	LENGTH (m)		WEIGHT (kgs)
		Closed	Open	
TRENCH0	Standard No. 0 Strut	0.32	0.47	4.0
TRENCH1	Standard No. 1 Strut	0.49	0.73	5.8
TRENCH2	Standard No. 2 Strut	0.69	1.09	7.7
TRENCH3	Standard No. 3 Strut	1.03	1.73	11.0

Struts are fully tested in-house from a company with over 40 years of Prop manufacturing experience and the capability to produce any specification of prop you may require.



Technical Information

- All props are manufactured to BS4074:2000.
- Sizes 1, 2, 3 supplied with captive inners.
- Safe working load: 3 tonnes, any size, any extension.
- Finished in one coat air drying.

The internet's No. 1 supply resource for BUILDERS, SCAFFOLDERS & HOMEOWNERS



Free delivery on all orders over £300



48hours delivery on items ordered before 12 pm